

FIBER MANAGEMENT

TERMINATION BOX

TERMINATION BOX

Termination box is suitable for jointing Fiber to Fiber pigtail and it protects Fiber optic splices and helps to distribute. The termination box is a wall mounting type or desktop type, which is mainly used in telecommunication equipment room and network equipment room.



TBA



Features

- TBA is designed in up-down bisection. Its installation is quite simple. By untightening one piece of fixing nut, it succeeds in opening the housing and allows Fiber cable and pigtails to pass in and out in one side. The termination box is made of high-strength polycarbonate plastic materials, which has mechanical strength.
- SLIDE-IN-LOCK OFST with its opening angle above 90degree makes it easy for installation and maintenance. When distribution of pigtail can not be determined (it is not used for the moment), it is possible to wind pigtail into clasp. Whenever it is needed, the connector could be installed outside of the housing, therefore it can connect termination equipment without connecting adapters.

THE ORDERING GUIDANCE

Type	Max. capacity(core)	Optical Fiber Splice Tray(OFST) (including heat shrinkable protective sleeve)	Measurement
TBA-06	6	1 piece of FOST with 6 cores	265x153x42
TBA-12	12	2 piece of FOST with 6 cores	265x153x42
TBA-18	18	3 piece of FOST with 6 cores	265x153x60
TBA-24	24	4 piece of FOST with 6 cores	265x153x60