

# FIBRE MANAGEMENT

## CABINETS

### WALL MOUNTED CABINETS

Strong and robust 19" wall mounted cabinet, with a lockable steel framed glass door for safety and security. Quick release hinges allow for easy access to the cabinet for loading equipment and cables, with gland plate covers on the top and bottom of the cabinet to allow for cable entry. The sides of the cabinet are ventilated to improve air flow.

#### Features

- 600mm wide.
- 6u, 9u, 12u and 15u 450mm deep.
- Sliding 19" mounting profiles front and rear.
- Standard ventilation top and bottom.
- Vented framed door with safety glass.
- Rear panel installation.
- Heavy duty construction – 60kg (UDL)
- Pre-assembled .
- Lockable side panels.
- Door opens 180degrees, hinged left or right.
- Built in cable strain relief positions .
- Grey – RAL7035.

#### Specifications

- Top and base panel 1.2mm
- Side panels 1.2mm
- Framework 1.2mm
- 19" mounting angles 1.5mm
- Matching lock configuration on side panels
- Individual lock on front door.
- Chassis support (L RAIL) Maximum load 20Kgs.  
One pair included
- Material thickness 1.2mm



Lockable side panels



Sliding mounting angles



Secure lock



Cable strain relief positions



Quick release door



Side latch



### ORDERING INFORMATION

Height	Depth	Width	Weight	Part No.
6U	450	600	20.5kg	SOFWC0106G
9U	450	600	24kg	SOFWC0109G
9U	600	600	28.5kg	SOFWC0209G
12U	450	600	27.5kg	SOFWC0112G
12U	600	600	32.5kg	SOFWC0212G
15U	450	600	31kg	SOFWC0115G

Height	Depth	Width	Weight	Part No.
15U	600	600	36kg	SOFWC0215G
18U	450	600	36.5kg	SOFWC0118G
18U	600	600	42kg	SOFWC0218G
22U	450	600	41.5kg	SOFWC0122G